



SPECIFICATIONS - DIMENSIONS (INCHES)

MODEL	GROOVES	ROPE SIZE	WLL (LBS) *	DIM A	DIM B	WEIGHT
8SA8-S1G19	1	Ø3/16	600	3.48	5.48	17.2 LBS
8SA8-S2G19	2	Ø3/16	600	3.71	5.71	17.7 LBS
8SA8-S3G19	3	Ø3/16	600	4.19	6.19	18.8 LBS
8SA8-S4G19	4	Ø3/16	1200	4.66	6.66	20.1 LBS
8SA8-S5G19	5	Ø3/16	1200	5.13	7.13	21.3 LBS
8SA8-S6G19	6	Ø3/16	1200	5.60	7.60	22.4 LBS
8SA8-S7G19	7	Ø3/16	1200	6.08	8.08	23.5 LBS
8SA8-S8G19	8	Ø3/16	1200	6.55	8.55	24.6 LBS
8SA8-S9G19	9	Ø3/16	1200	7.02	9.02	25.7 LBS
8SA8-S1G25	1	Ø1/4	600	3.48	5.48	17.2 LBS
8SA8-S2G25	2	Ø1/4	600	3.71	5.71	17.7 LBS
8SA8-S3G25	3	Ø1/4	600	4.19	6.19	18.8 LBS
8SA8-S4G25	4	Ø1/4	1200	4.66	6.66	20.0 LBS
8SA8-S5G25	5	Ø1/4	1200	5.13	7.13	21.1 LBS
8SA8-S6G25	6	Ø1/4	1200	5.60	7.60	22.2 LBS
8SA8-S7G25	7	Ø1/4	1200	6.08	8.08	23.3 LBS
8SA8-S8G25	8	Ø1/4	1200	6.55	8.55	24.4 LBS
8SA8-S9G25	9	Ø1/4	1200	7.02	9.02	25.4 LBS

NOTES:

- WORKING LOAD LIMITS (WLL) *:
 - MAY EXCEED CAPACITY OF THE ROPE.
 - USE ROPE MANUFACTURER'S RATING AND SAFETY FACTOR TO DETERMINE LOAD LIMIT.
 - ARE FOR UNITS MOUNTED USING STANDARD DESIGN AND CONSTRUCTION.
 - ARE BASED ON CABLES WRAPPED 90 DEGREES AROUND THE SHEAVES.
 - CONTACT FACTORY FOR OTHER CONDITIONS.
- MOUNTING HARDWARE MUST BE DISTRIBUTED EVENLY ON BOTH ANGLES.
 - MINIMUM OF 4 ATTACHMENT POINTS.
- CONTACT FACTORY FOR NON-STANDARD GROOVE OR MOUNTING REQUIREMENTS.

4 GROOVE MODEL SHOWN

NOT FOR CONSTRUCTION

THIS PRINT IS THE PROPERTY OF THERN AND MUST NOT BE REPRODUCED EITHER IN FULL OR IN PART WITHOUT WRITTEN APPROVAL BY THERN.

**THERN
STAGE
EQUIPMENT**

5712 INDUSTRIAL PARK ROAD
WINONA, MN 55987
PHONE 1-800-553-2204
FAX 1-507-454-5882

DESCRIPTION: **BLOCK W/ ANGLES - BALL BEARING**
 TOLERANCES UNLESS SPECIFIED:
 FRACTIONAL ANGLES ±.015
 DECIMAL ANGLES ±.005
 DO NOT SCALE DRAWING

MODEL: **8SA8-S SERIES**
 DRAWING NUMBER: **C4480**

DRAWN BY: JCA DATE: 6/30/2008 SCALE: N/A WEIGHT: N/A REVISION: N/A SHEET 1 OF 1