



- NOTES:
- WORKING LOAD LIMITS (WLL) \* :
    - MAY EXCEED CAPACITY OF THE ROPE.
    - USE ROPE MANUFACTURER'S RATING AND SAFETY FACTOR TO DETERMINE LOAD LIMIT.
    - ARE FOR UNITS MOUNTED USING STANDARD DESIGN AND CONSTRUCTION.
    - ARE BASED ON CABLES WRAPPED 90 DEGREES AROUND THE SHEAVES.
    - CONTACT FACTORY FOR OTHER CONDITIONS.
  - MOUNTING HARDWARE MUST BE DISTRIBUTED EVENLY ON BOTH ANGLES.
    - MINIMUM OF 4 ATTACHMENT POINTS.
    - POSITION ANGLES CENTERED BETWEEN MOUNTING POINTS.
  - UNDERHUNG BLOCKS MAY NEED TO BE WELDED TO HEAD BEAMS AFTER FINAL ALIGNMENT. MOUNTING CLIP ANGLES ARE RECOMMENDED. CONTACT FACTORY WITH BEAM DIMENSIONS.
  - CONTACT FACTORY FOR NON-STANDARD GROOVE OR MOUNTING REQUIREMENTS.

MODEL	GROOVES	ROPE SIZE	HAND LINE	WLL (LBS) *	WEIGHT
8SH12-N8G19DP	8	Ø3/16	Ø3/4	3000	63.0 LBS
8SH12-N8G25DP	8	Ø1/4	Ø3/4	3000	62.7 LBS

NOT FOR CONSTRUCTION

**TSE**  
TERRAZZO SPECIAL EQUIPMENT

8510 INDUSTRIAL PARK ROAD  
WINONA, MN 55907  
PHONE: 507-535-2204  
FAX: 507-535-2204  
TOLERANCES UNLESS SPECIFIED  
DO NOT SCALE DRAWINGS

NAME: HEAD BLOCK - UNDERHUNG  
IDENTIFICATION: 8SH12 SERIES  
D3517

DESIGNER: JCA  
DATE: 11/4/2009  
PROJECT: N/A  
CHECK: NTS  
REVISION: N/A  
SHEET OF 1