



**NOTES:**

- WORKING LOAD LIMITS (WLL) \* :
  - MAY EXCEED CAPACITY OF THE ROPE.
  - USE ROPE MANUFACTURER'S RATING AND SAFETY FACTOR TO DETERMINE LOAD LIMIT.
  - ARE FOR UNITS MOUNTED USING STANDARD DESIGN AND CONSTRUCTION.
  - ARE BASED ON CABLES WRAPPED 90 DEGREES AROUND THE SHEAVES.
  - CONTACT FACTORY FOR OTHER CONDITIONS.
- MOUNTING HARDWARE MUST BE DISTRIBUTED EVENLY ON BOTH ANGLES.
  - MINIMUM OF 4 ATTACHMENT POINTS.
  - POSITION ANGLES CENTERED BETWEEN MOUNTING POINTS.
- CONTACT FACTORY FOR NON-STANDARD GROOVE OR MOUNTING REQUIREMENTS.

MODEL	GROOVES	ROPE SIZE	HAND LINE	WLL (LBS) *	WEIGHT
8SH12-R8G19DP	8	$\phi 3/16$	$\phi 3/4$	3000	64.7 LBS
8SH12-R8G25DP	8	$\phi 1/4$	$\phi 3/4$	3000	64.4 LBS

**NOT FOR CONSTRUCTION**

THIS PRINT IS THE PROPERTY OF THERM AND MUST NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT WRITTEN APPROVAL BY THERM.

**THERM**  
**CHINA**  
**EQUIPMENT**

8513 INDUSTRIAL PARK ROAD  
 WINONA, MN 55987  
 PHONE: 507-535-2204  
 FAX: 507-535-2204  
 TOLERANCES UNLESS SPECIFIED  
 DO NOT SCALE DRAWINGS

DESCRIPTION: HEAD BLOCK - UPRIGHT

DATE: 11/4/2009

QUANTITY: 8SH12 SERIES

IDENTIFICATION: D3513

DESIGNER: JCA

DATE: 11/4/2009

PROJECT: 64.4 lbmass

LOCK: NTS

REVISION: NTS

SHEET OF 1