



NOTES:

- WORKING LOAD LIMITS (WLL) * :
 - MAY EXCEED CAPACITY OF THE ROPE.
 - USE ROPE MANUFACTURER'S RATING AND SAFETY FACTOR TO DETERMINE LOAD LIMIT.
 - ARE FOR UNITS MOUNTED USING STANDARD DESIGN AND CONSTRUCTION.
 - ARE BASED ON CABLES WRAPPED 90 DEGREES AROUND THE SHEAVES.
 - CONTACT FACTORY FOR OTHER CONDITIONS.
- MOUNTING HARDWARE MUST BE DISTRIBUTED EVENLY ON BOTH ANGLES.
 - MINIMUM OF 4 ATTACHMENT POINTS.
 - POSITION ANGLES CENTERED BETWEEN MOUNTING POINTS.
- CONTACT FACTORY FOR NON-STANDARD GROOVE OR MOUNTING REQUIREMENTS.

MODEL	GROOVES	ROPE SIZE	HAND LINE	WLL (LBS) *	WEIGHT
8SH12-R8G19SP	8	$\phi 3/16$	$\phi 3/4$	3000	60.8 LBS
8SH12-R8G25SP	8	$\phi 1/4$	$\phi 3/4$	3000	60.5 LBS

NOT FOR CONSTRUCTION

THIS PRINT IS THE PROPERTY OF THERM AND MUST NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, WITHOUT WRITTEN APPROVAL BY THERM.

TSE
THERM
STEEL
EQUIPMENT

8515 INDUSTRIAL PARK ROAD
WINONA, MN 55907
TEL: 507-535-2204
FAX: 507-535-2204

TOLERANCES UNLESS SPECIFIED
DO NOT SCALE DRAWINGS

DESCRIPTION	HEAD BLOCK - UPRIGHT
DATE	11/4/2009
QUANTITY	8SH12 SERIES
REVISION	D3511

DESIGNER	JCA	CHECKED	N/A	PROJECT	2	DATE	11/4/2009	SCALE	N/A	REVISION	NTS	SHEET	OF 1
----------	-----	---------	-----	---------	---	------	-----------	-------	-----	----------	-----	-------	------